

# LIFTING CAPACITY.

## MX14G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\*

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.0*	5.0*	5.0*	4.3*	3.9	4.3*												
6.0	3.9*	3.9*	3.9*	4.4*	4.1	4.4*	3.2	2.8	4.5*	2.3	2.0	3.9*						
4.0	5.1*	5.1*	5.1*	4.4	3.7	5.4*	3.0	2.6	5.4*	2.2	1.9	5.1*	1.7	1.4	4.0*			
2.0	5.8	4.8	12.4*	3.7	3.1	9.7*	2.7	2.3	7.7*	2.0	1.7	6.0	1.6	1.3	4.6	1.3	1.1	2.5*
0.0	5.1	4.1	13.3*	3.3	2.8	10.2*	2.4	2.0	8.0	1.9	1.6	5.8	1.5	1.2	4.5			
-2.0	5.2	4.2	14.3*	3.3	2.7	10.4*	2.4	2.0	7.9	1.9	1.5	5.8						
-3.0	5.4	4.4	14.1*	3.4	2.8	9.8*	2.5	2.1	6.8*									

## MX14G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS 2 X A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\*

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.0*	5.0*	5.0*	4.3*	4.1	4.3*												
6.0	3.9*	3.9*	3.9*	4.4*	4.3	4.4*	4.2	2.9	4.5*	3.1	2.1	3.9*						
4.0	5.1*	5.1*	5.1*	5.4*	4.0	5.4*	4.0	2.8	5.4*	3.0	2.0	5.1*	2.3	1.5	4.0*			
2.0	8.2	5.1	12.4*	5.2	3.4	9.7*	3.7	2.4	7.7*	2.8	1.8	6.3*	2.2	1.4	5.3	1.8	1.2	2.5*
0.0	7.5	4.5	13.3*	4.7	3.0	10.2*	3.4	2.2	8.0*	2.6	1.7	6.5*	2.1	1.3	5.2			
-2.0	7.5	4.5	14.3*	4.7	2.9	10.4*	3.4	2.1	8.0*	2.6	1.7	5.9*						
-3.0	7.7	4.7	14.1*	4.8	3.0	9.8*	3.5	2.2	6.8*									

## MX14G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A3, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\*

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.0*	5.0*	5.0*	4.4*	4.2*	4.3*												
6.0	3.9*	3.9*	3.9*	4.4*	4.3	4.4*	4.5*	3.0	4.5*	3.9*	2.1	3.9*						
4.0	5.1*	5.1*	5.1*	5.4*	4.0	5.4*	5.4*	2.8	5.4*	4.1	2.1	5.1*	3.1	1.5	4.0*			
2.0	12.4*	5.2	12.4*	7.3	3.4	9.7*	5.1	2.5	7.7*	3.8	1.9	6.2	3.0	1.5	4.8	2.5*	1.2	2.5*
0.0	11.5	4.5	13.3*	6.8	3.0	10.2*	4.8	2.2	8.0*	3.7	1.7	6.0	2.9	1.4	4.7			
-2.0	11.6	4.6	14.3*	6.8	3.0	10.4*	4.8	2.2	8.0*	3.6	1.7	5.9*						
-3.0	11.8	4.8	14.1*	6.9	3.1	9.8*	4.9	2.3	6.8*									

## MX14G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A4, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\*

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.0*	5.0*	5.0*	4.3*	4.2*	4.3*												
6.0	3.9*	3.9*	3.9*	4.4*	4.4	4.4*	4.5*	3.0	4.5*	3.9*	2.2	3.9*						
4.0	5.1*	5.1*	5.1*	5.4*	4.1	5.4*	5.4*	2.8	5.4*	5.1*	2.1	5.1*	4.0*	1.6	4.0*			
2.0	12.4*	5.3	12.4*	9.7*	3.5	9.7*	6.7	2.5	7.7*	5.0	1.9	6.3*	3.9	1.5	5.0	2.5*	1.2	2.5*
0.0	13.3*	4.6	13.3*	9.3	3.1	10.2*	6.3	2.3	8.0*	4.8	1.7	6.2	3.8	1.4	4.9			
-2.0	14.3*	4.7	14.3*	9.2	3.0	10.4*	6.3	2.2	8.0*	4.7	1.7	5.9*						
-3.0	14.1*	4.8	14.1*	9.3	3.1	9.8*	6.4	2.3	6.8*									

\* Table values are in accordance with ISO 10567 (75% of stability or 87% of hydraulic capacity). If lifting via the standard mounted lifting hook, allow for a maximum of 12 tons. If lifting without quick hitch and directly in the outer hole in the slewing arm, values can be used by adding approx. 150 kg.



**F:** Lift 360° with support raised



**AL:** Lift along the length of the machine with the support lowered



**AQ:** Lift across the machine with the support lowered

**MX16G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.4	4.7	5.7*	3.6	3.2	5.3*									
6.0	4.2*	4.2*	4.2*	5.1	4.7	5.1*	3.7	3.2	5.4*	2.7	2.3	5.3*	2.0	1.7	4.2*			
4.0	7.1*	6.9	7.1*	4.9	4.2	7.0*	3.4	3.0	6.8*	2.6	2.2	6.2*	2.0	1.7	5.3			
2.0	7.3	6.2	11.3*	4.2	3.6	11.4*	3.0	2.6	8.6*	2.3	2.0	6.6	1.8	1.5	5.1	1.4	1.1	3.7*
0.0	6.0	4.9	14.7*	3.8	3.1	12.1*	2.8	2.3	8.7	2.1	1.8	6.4	1.7	1.4	5.0			
-2.0	5.9	4.8	16.9*	3.7	3.1	12.3*	2.7	2.3	8.7	2.1	1.8	6.3	1.7	1.4	5.0			
-4.0	6.3	5.3	15.3*	4.1	3.4	10.3*												

**MX16G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS 2 X A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.7*	4.9	5.7*	4.7	3.3	5.3*									
6.0	4.2*	4.2*	4.2*	5.1*	4.9	5.1*	4.8	3.4	5.4*	3.5	2.5	5.3*	2.7	1.8	4.2*			
4.0	7.1*	7.1*	7.1*	6.4	4.4	7.0*	4.5	3.1	6.8*	3.4	2.3	6.2*	2.6	1.8	5.5*			
2.0	10.0	6.5	11.3*	5.7	3.8	11.4*	4.1	2.7	8.6*	3.1	2.1	7.0*	2.5	1.7	5.8	1.9	1.2	3.7*
0.0	8.5	5.2	14.7*	5.2	3.3	12.1*	3.8	2.5	9.5*	2.9	1.9	7.2	2.4	1.5	5.7			
-2.0	8.4	5.1	16.9*	5.2	3.3	12.3*	3.7	2.4	9.6*	2.9	1.9	7.2	2.4	1.5	5.4*			
-4.0	8.9	5.6	15.3*	5.6	3.7	10.3*												

**MX16G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A3, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.7*	4.9	5.7*	5.3*	3.4	5.3*									
6.0	4.2*	4.2*	4.2*	5.1*	4.9	5.1*	5.4*	3.4	5.4*	4.7	2.5	5.3*	3.6	1.9	4.2*			
4.0	7.1*	7.1*	7.1*	7.0	4.5	7.0*	6.1	3.2	6.8*	4.5	2.4	6.2*	3.5	1.8	5.5			
2.0	11.3*	6.6	11.3*	8.1	3.8	11.4*	5.6	2.8	8.6*	4.3	2.1	6.8	3.4	1.7	5.3	2.6	1.3	3.7*
0.0	12.9*	5.3	14.7*	7.5	3.4	12.1*	5.3	2.5	8.8	4.1	2.0	6.5	3.2	1.6	5.2			
-2.0	12.7	5.2	16.9*	7.5	3.4	12.3*	5.2	2.5	8.8	4.0	1.9	6.5	3.2	1.6	5.1			
-4.0	13.4	5.6	15.3*	7.9	3.7	10.3*												

**MX16G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A4, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.7*	5.0	5.7*	5.3*	3.4	5.3*									
6.0	4.2*	4.2*	4.2*	5.1*	5.0	5.1*	5.4*	3.5	5.4*	5.3*	2.5	5.3*	4.2*	1.9	4.2*			
4.0	7.1*	7.1*	7.1*	7.0*	4.5	7.0*	6.8*	3.2	6.8*	5.7	2.4	6.2*	4.4	1.8	5.5*			
2.0	11.3*	6.6	11.3*	10.7	3.9	11.4*	7.2	2.8	8.6*	5.4	2.2	6.9	4.3	1.7	5.4	3.3	1.3	3.7*
0.0	14.7*	5.4	14.7*	10.1	3.4	12.4*	6.9	2.5	9.1	5.2	2.0	6.7	4.2	1.6	5.3			
-2.0	16.9*	5.3	16.9*	10.0	3.4	12.3*	6.8	2.5	9.0	5.2	1.9	6.7	4.1	1.6	5.3			
-4.0	15.3*	5.7	15.3*	10.3*	3.8	10.3*												

\* Table values are in accordance with ISO 10567 (75% of stability or 87% of hydraulic capacity). If lifting via the standard mounted lifting hook, allow for a maximum of 12 tons. If lifting without quick hitch and directly in the outer hole in the slewing arm, values can be used by adding approx. 150 kg.



**F:** Lift 360° with support raised



**AL:** Lift along the length of the machine with the support lowered



**AQ:** Lift across the machine with the support lowered

**MX17G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.7*	5.3	5.7*	4.1	3.6	5.3*									
6.0	4.2*	4.2*	4.2*	5.1*	5.1*	5.1*	4.2	3.7	5.4*	3.1	2.7	5.3*	2.3	2.0	4.2*			
4.0	7.1*	7.1*	7.1*	5.5	4.8	7.0*	3.9	3.4	6.8*	2.9	2.6	6.2*	2.3	2.0	5.4*			
2.0	8.3	7.1	11.3*	4.9	4.2	11.4*	3.5	3.0	8.5*	2.7	2.3	6.9*	2.2	1.8	5.7	1.6	1.4	3.7*
0.0	7.0	5.8	14.7*	4.4	3.7	12.1	3.2	2.8	9.5*	2.5	2.2	7.1	2.0	1.7	5.6			
-2.0	6.8	5.7	16.9*	4.4	3.7	12.3*	3.2	2.7	9.6*	2.5	2.1	7.0	2.0	1.7	5.4*			
-4.0	7.3	6.1	15.2*	4.7	4.0	10.3*												

**MX17G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS 2 X A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.7*	5.5	5.7*	5.3*	3.8	5.3*									
6.0	4.2*	4.2*	4.2*	5.1*	5.1*	5.1*	5.3	3.8	5.4*	4.0	2.8	5.3*	3.0	2.1	4.2*			
4.0	7.1*	7.1*	7.1*	7.0*	5.0	7.0*	5.0	3.6	6.8*	3.8	2.7	6.2*	3.0	2.1	5.4*			
2.0	11.1	7.4	11.3*	6.5	4.4	11.4*	4.6	3.2	8.5*	3.6	2.5	6.9*	2.8	2.0	6.1*	2.2	1.5	3.7*
0.0	9.7	6.1	14.7*	6.0	3.9	12.1*	4.3	2.9	9.5*	3.4	2.3	7.8*	2.7	1.8	6.2			
-2.0	9.5	6.0	16.9*	5.9	3.9	12.3*	4.3	2.9	9.6*	3.3	2.2	7.7*	2.7	1.8	5.4			
-4.0	10.1	6.5	15.2*	6.3	4.3	10.3*												

**MX17G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A3, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.7*	5.5	5.7*	5.3*	3.8	5.3*									
6.0	4.2*	4.2*	4.2*	5.1*	5.1*	5.1*	5.4*	3.9	5.4*	5.2	2.9	5.3*	4.0	2.2	4.2*			
4.0	7.1*	7.1*	7.1*	7.0*	5.1*	7.0*	6.7	3.6	6.8*	5.0	2.7	6.2*	3.9	2.1	5.4*			
2.0	11.3*	7.4	11.3*	9.0	4.4	11.4*	6.2	3.2	8.5*	4.8	2.5	6.9*	3.8	2.0	5.8	2.9	1.5	3.7*
0.0	14.4	6.2	14.7*	8.4	4.0	12.1*	5.9	3.0	9.5*	4.6	12.3	7.2	3.7	1.9	5.7			
-2.0	14.3	6.1	16.9*	8.4	3.9	12.3*	5.9	2.9	9.6*	4.5	2.3	7.2	3.6	1.9	5.4*			
-4.0	14.9	6.5	15.2*	8.8	4.3	10.3*												

**MX17G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A4, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter

H	3.0			4.0			5.0			6.0			7.0			Max.		
	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	5.6*	5.6*	5.6*	5.7*	5.6	5.7*	5.3*	3.9	5.3*									
6.0	4.2*	4.2*	4.2*	5.1*	5.1*	5.1*	5.4*	3.9	5.4*	5.3*	2.9	5.3*	4.2*	2.2	4.2*			
4.0	7.1*	7.1*	7.1*	7.0*	5.1	7.0*	6.8*	3.6	6.8*	6.2*	2.8	6.2*	4.9	2.1	5.4*			
2.0	11.3*	7.5	11.3*	11.4*	4.5	11.4*	8.0	3.3	8.5*	6.0	2.5	6.9*	4.7	2.0	6.0	3.6	1.5	3.7*
0.0	14.7*	6.3	14.7*	11.2	4.0	12.1*	7.7	3.0	9.5*	5.8	2.3	7.4	4.6	1.9	5.8			
-2.0	16.9*	6.2	16.9*	11.1	4.0	12.3*	7.6	2.9	9.6*	5.7	2.3	7.3	4.6	1.9	5.4*			
-4.0	15.2*	6.6	15.2*	10.3*	4.4	10.3*												

\* Table values are in accordance with ISO 10567 (75% of stability or 87% of hydraulic capacity). If lifting via the standard mounted lifting hook, allow for a maximum of 12 tons. If lifting without quick hitch and directly in the outer hole in the slewing arm, values can be used by adding approx. 150 kg.

**MX18G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter																		
	3.0			4.0			5.0			6.0			7.0			Max.		
H	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	6.7*	6.7*	6.7*	6.1	5.3	6.9*	4.2	3.7	6.8*									
6.0	5.6*	5.6*	5.6*	6.0	5.2	6.5*	4.1	3.6	6.8*	3.0	2.6	6.0*	2.3	2.0	5.5*			
4.0	8.7	7.4	10.3*	5.3	4.5	9.6*	3.7	3.2	7.6*	2.8	2.4	6.4*	2.2	1.9	5.8*			
2.0	7.5	6.3	11.7*	4.5	3.8	11.3*	3.3	2.8	9.0*	2.5	2.1	7.2	2.0	1.7	5.6	1.4	1.2	3.9*
0.0	6.5	5.3	14.4*	4.0	3.3	11.7*	3.0	2.5	9.2*	2.3	1.9	6.9	1.9	1.6	5.4			
-2.0	6.5	5.3	16.5*	4.0	3.4	11.9*	2.9	2.4	9.3*	2.3	1.9	6.8	1.8	1.5	5.4			
-4.0	6.9	5.7	16.2*	4.4	3.7	11.2*	3.2	2.7	7.9*									

**MX18G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS 2 X A1, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter																		
	3.0			4.0			5.0			6.0			7.0			Max.		
H	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	6.7*	6.7*	6.7*	6.9*	5.6	6.9*	5.3	3.8	6.8*									
6.0	5.6*	5.6*	5.6*	6.5*	5.4	6.5*	5.3	3.8	6.8*	3.9	2.8	6.0*	3.0	2.1	5.5*			
4.0	10.3*	7.7	10.3*	6.9	4.8	9.6*	4.9	3.4	7.6*	3.7	2.6	6.4*	2.9	2.0	5.8*			
2.0	10.3	6.6	11.7*	6.1	4.0	11.3*	4.4	2.9	9.0*	3.4	2.3	7.2*	2.7	1.8	6.2*	1.9	1.2	3.9*
0.0	9.2	5.6	14.4*	5.6	3.6	11.7*	4.1	2.6	9.2*	3.2	2.1	7.5*	2.5	1.7	6.1			
-2.0	9.1	5.6	16.5*	5.6	3.6	11.9*	4.0	2.6	9.3*	3.1	2.0	7.7	2.5	1.6	6.0			
-4.0	9.7	6.1	16.2*	6.0	3.9	11.2*	4.3	2.8	7.9*									

**MX18G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A3, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter																		
	3.0			4.0			5.0			6.0			7.0			Max.		
H	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	6.7*	6.7*	6.7*	6.9*	5.6	6.9*	6.8*	3.9	6.8*									
6.0	5.6*	5.6*	5.6*	6.5*	5.5	6.5*	6.8*	3.8	6.8*	5.1	2.8	6.0*	3.9	2.1	5.5*			
4.0	10.3*	7.8	10.3*	9.5	4.8	9.6*	6.5	3.4	7.6*	4.9	2.6	6.4*	3.8	12.0	5.8			
2.0	11.7*	6.7	11.7*	8.6	4.1	11.3*	6.0	3.0	9.0*	4.6	2.3	7.2*	3.6	1.8	5.7	2.6	1.3	3.9*
0.0	13.8	5.7	14.4*	8.0	3.6	11.7*	5.7	2.7	9.2*	4.3	2.1	7.0	3.5	1.7	5.5			
-2.0	13.8	5.7	16.5*	8.0	3.6	11.9*	5.6	2.6	9.3*	4.3	2.1	6.9	3.5	1.7	5.5			
-4.0	14.4	6.1	16.2*	8.4	4.0	11.2*	5.9	2.9	7.9*									

**MX18G : MAX LIFTING CAPACITY IN TONNE WITH CHASSIS A4, DIPPER 2.5 M. WEIGHT QUICK HITCH 150 KG. ISO 10567\***

Reach in Meter																		
	3.0			4.0			5.0			6.0			7.0			Max.		
H	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL	AQ	F	AL
8.0	6.7*	6.7*	6.7*	6.9*	5.7	6.9*	6.8*	3.9	6.8*									
6.0	5.6*	5.6*	5.6*	6.5*	5.5	6.5*	6.8*	3.8	6.8*	6.0	2.8	6.0*	4.9	2.1	5.5*			
4.0	10.3*	7.9	10.3*	9.6*	4.9	9.6*	7.6*	3.5	7.6*	6.2	2.6	6.4*	4.8	2.0	5.8*			
2.0	11.7*	6.8	11.7*	11.3*	4.1	11.3*	7.7	3.0	9.0*	5.8	2.3	7.2*	4.6	1.9	5.8	3.3	1.3	3.9*
0.0	14.4*	5.8	14.4*	10.8	3.7	11.7*	7.4	2.7	9.2*	5.6	2.1	7.2	4.4	1.7	5.7			
-2.0	16.5*	5.8	16.5*	10.8	3.7	11.9*	7.3	2.7	9.3*	5.5	2.1	7.1	4.4	1.7	5.6			
-4.0	16.2*	6.2	16.2*	11.2*	4.0	11.2*	7.6	2.9	7.9*									

\* Table values are in accordance with ISO 10567 (75% of stability or 87% of hydraulic capacity). If lifting via the standard mounted lifting hook, allow for a maximum of 12 tons. If lifting without quick hitch and directly in the outer hole in the slewing arm, values can be used by adding approx. 150 kg.

