%906G



UNIQUE FEATURES AND STRONG PERFORMANCE MAKE THESE THE MOST EFFICIENT BACKHOES ON THE MARKET.

- Pivot steering with load transfer
- Excavator with up to 280° working area
- Loader with strong Z-kinematics
 - Comfortable, silent and powerful
- Two machines in one the operator can carry out many varied tasks
- Electronically controlled double command



Email: hydrema@hydrema.com www.hydrema.com



TECHNICAL DATA

CHASSIS

Heavy-duty robot-welded articulated chassis with fixed axles. Pivot joint with pendulum bar and double hydraulic stabilisers with the option of hydraulic locking of the oscillating movement. Oscillating angle: +/- 11°.

TRANSMISSION

DANA 6/3 gear fully automatic electronically controlled transmission. Double "kick down". Torque converter with torque increase. No. of gears: 6 forward 3 reverse. Permanent 4-wheel drive.

HYDRAULIC SYSTEM

Electronically controlled Double Command with Flow Sharing and Mode Control for all models.

Load sensing system with variable pump. 163 l/min and 240 bar.

FUEL

Diesel: 155 I. fuel tank. AdBlue: 14 I. tank.

AXLES

Fixed, rigid axles with hub reduction. Automatic limited slip differential lock on front axle, 100% electro-hydraulic differential lock on rear axle.

ENGINE

Cummins B4.5 Stage 5 engine with DOC, DPF and SCR catalysts with Ad-Blue additive. 4.5 litre, 16 valve common rail turbo diesel engine with intercooler and electronically variable turbo charger. Can run on biodiesel (HVO).

Max. 122 hp (90 kW) Torque: 470 Nm at 1500 rpm.

STEERING

Hydrostatic steering with Load Sensing hydraulics and two double acting cylinders with end brake. Pivot steering angle: +/- 35°.

DIMENSIONS

| | | 906G |
|-----------------------------|----|------|
| Total weight | kg | 9200 |
| Width over standard tyres | mm | 2300 |
| Turning radius | mm | 5600 |
| Slew angle, excavator | 0 | 280 |
| Digging depth, excavator | mm | 4810 |
| Reach, excavator | mm | 6130 |
| Lifting capacity, excavator | kg | 1450 |
| Shovel volume, loader | m³ | 1.40 |
| Width, standard shovel | mm | 2380 |
| Lifting capacity, loader | kg | 4500 |
| Height, shovel pivot | mm | 3670 |

udstyr - 01/2025



MANY NEW BENEFITS IN THE G-SERIES, E.G:

Updated cabin with cooling box,

multi-adjustable armrests and

new rear window layout

of functions in the joysticks

Remote controlled bonnet as well

Hydrema Telematics as standard

"Follow me home-" and "welcome light"

Individual adjustment

